

## Safety Data Sheet

# **Lithium-Ion Battery**

Version 1.0 Issue date: 02/12/2019

## **Section 1: Product and Company Identification**

1.1 Product identifier:

Product Form: Battery

Product name: FL-Series - Li-ion Robot batteries

1.2 Relevant identified uses of the substance and uses advised against:

1.2.1 Identified uses: Cyclic use

1.2.2 Uses advised against: Automotive, motorcycle, commercial applications

1.3 Details of the supplier of the safety data sheet:

Supplier: FULBAT S.a.s

Address: 23 bis rue Edouard Nieuport

92150 Suresnes

**France** 

Telephone: +33 1 83 62 45 55

1.4 Emergency telephone Number:

CHEMTREC (US, Canada & Mexico) 0086-1-800-424-9300 CHEMTREC (International) 0086-1-703-527-3887

Available outside office hours? YES NO X

## **Section 2: Hazard Identification**

This is a product that fulfills a certain function in solid state with specific shape without discharging any chemical substance in its use and has no obligation to write MSDS. Since this document contains the precautions for safe handling related to its materials or chemical substances consisting of this product, please note that this overall information is irrelevant to this product.

#### 2.1 Classification of the substance or mixture:

#### 2.1.1 Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Not classified

#### 2.1.2 Additional information:

## Classification of the substance or mixture.

**Preparation Hazards and Classification:** The product is a Lithium ion cell or battery and is therefore classified as an article and is not hazardous when used according to the recommendations of the manufacturer. The hazard is associated with the contents of the cell or battery. Under recommended use conditions, the electrode materials and liquid electrolyte are non-reactive provided that the cell or battery integrity remains and the seals

Product Name: Lithium-Ion Battery

MSDS Page 1 of 9



remain intact. The potential for exposure should not exist unless the cell or battery leaks, is exposed to high temperatures or is mechanically, electrically or physically abused/damaged. If the cell or battery is compromised and starts to leak, based upon the battery ingredients, the contents are classified as Hazardous.

#### **Hazardous materials Information**

Label (HMIS)

Health: Not available

Flammability: Not available Physical Hazard: Not available

#### 2.2 Label elements:

Hazard pictograms: Not applicable

Signal word: Not applicable

**Hazard statement:** Not applicable **Precautionary statements:** Not

applicable

**Supplemental Hazard information** 

(EU): Not applicable

## 2.3 Other hazards:

Appearance, Color and Odor: Solid object with no odor.

**Primary Routes(s) of Exposure:** These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell or pack is mechanically, thermally, electrically or physically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by inhalation, ingestion, eye contact and skin contact.

#### Potential Health Effect(s):

## Acute (short term):

If this cell or pack has been ruptured, the electrolyte solution contained within the cell would be corrosive and can cause burns to skin and eyes.

**Inhalation:** Inhalation of materials from a sealed cell is not an expected route of exposure. Vapors or mists from a ruptured cell may cause respiratory irritation.

**Ingestion:** Swallowing of materials from a sealed cell is not an expected route of exposure. Swallowing the contents of an open cell can cause serious chemical burns to mouth, esophagus, and gastrointestinal tract.

**Skin:** Contact between the cell and skin will not cause any harm. Skin contact with the contents of an open cell can cause severe irritation or burns to the skin.

**Eye:** Contact between the cell and the eye will not cause any harm. Eye contact with the contents of an open cell can cause severe irritation or burns to the eye.

**Interactions with other chemicals:** Immersion in high conductivity liquids may cause corrosion and breaching of the cell or battery enclosure. The electrolyte solution inside of the cells may react with alkaline (basic) materials and present a flammability hazard.

Product Name: Lithium-Ion Battery

MSDS Page 2 of 9



#### **Potential Environmental Effects:**

Not Available.

## Section 3: Composition/Information on Ingredients

#### **Further Information**

Because of the cell structure the dangerous ingredients will not be available if used properly.

Component	CAS No.	Weight (%)
Graphite	7782-42-5	15~25
Lithium nickelate	12031-65-1	15~25
Iron	7439-89-6	10~20
Lithium manganese oxide	12057-17-9	5~15
Lithium cobaltite	12190-79-3	1~10
Copper	7440-50-8	1~10
Dimethyl carbonate	616-38-6	1~10
Aluminium Foil	7429-90-5	1~10
Polyethylene	9002-88-4	1~10
Carbon black	1333-86-4	0.1~1
Nickel	7440-02-0	0.1~1
Lithium carbonate	554-13-2	0.1~1
1-Methyl-2-pyrrolidinone	872-50-4	0.1~1

## **Section 4: First-Aid Measures**

In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out corrosive fumes/gases and pungent odors.

In all case, seek immediate medical attention,

**Eye contact:** Flush with plenty of water (eyelids-held open) for at least 15 minutes **Skin contact:** Remove all contaminated clothing and flush affected areas with plenty of

water and sop for at least 15minutes.

**Ingestion:** Dilute by giving plenty of water and get immediate medical attention.

Assure that the victim does not aspirate vomited material by use of positional drainage.

Assure that mucus does not obstruct the airway.

Do not give anything by mouth to an unconscious person

**Inhalation:** Remove to fresh air and ventilate the contaminated area.

Give oxygen or artificial respiration if needed.

Product Name: Lithium-Ion Battery

MSDS Page 3 of 9



## **Section 5: Fire-Fighting Measures**

## Extinguishing media:

- When the scale of the fire is small, use a HFC (hydrofluorocarbon) clean-agent fire extinguisher or alcohol
  resistant foam fire extinguishers. (In case of battery overheating, wear protective gear and immerse heated
  battery in water)
- In case of large fire, use large amount of water to extinguish.

## Special hazards arising from the substance or mixture:

- Flammable gas leaks before ignition and then the product ignites.

## Advice for firefighters:

- The ignited battery has a high temperature, so there is a risk of additional ignition even if the fire is extinguished at early stage. Sprinkle a large amount of water until the battery temperature drops to normal temperature.
- If the battery is ignited in multi-stacked condition, multi-stack should be disassembled and then extinguished so that heat is not transferred between batteries
- In the event of a battery fire, cool it by spraying water directly on the battery.
- When handling a overheated battery, wear heat-resistant protective equipment.

#### Section 6: Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures for

#### non-emergency personnel:

Protective equipment: Use personal protective equipment, see Section 8

#### Emergency procedures :

- In case of cell damage, possible release of dangerous substances and a flammable gas mixture.
- Eliminate all ignition sources.
- Please note that materials and conditions to avoid.
- Battery may emit electrolyte if charging or discharging rates exceed manufacturer's recommendations or if pack has been breached.
- Move battery to well ventilated area to prevent gas accumulation.

## For emergency responders

- Eliminate all ignition sources.
- Please note that materials and conditions to avoid.
- Move battery to well ventilated area to prevent gas accumulation.

## 6.2 Environmental precautions:

- Avoid release to the environment.
- Prevent entry into waterways, sewers, basements or confined areas.

## 6.3 Methods and material for containment and cleaning up for

containment: Not available

#### For cleaning up:

- Cover with Dry earth, Dry sand or other non-combustible material and put on the plastic sheet to minimize

Product Name: Lithium-Ion Battery

MSDS Page 4 of 9



spreading or contact with rain.

- Move battery to well ventilated area to prevent gas accumulation.
- Dispose in accordance with applicable local, state and federal regulations.

Other information: Not available

## 6.4 Reference to other sections

- See also sections 8 and 13 of the Safety Data Sheet.

## Section 7: Handling and Storage

The batteries should not be opened destroyed nor incinerated since they may leak or rupture and release in the environment the ingredients they contain.

Handling	Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e.metal) goods. D				
	not directly heat or solder. Do not throw into fire. Do not mix batteries of different types. Do not				
	mix new and used batteries. Keep batteries in non-conductive (i.e. plastic) trays.				
Storage	Store in a cool (preferably below 30°C) and ventilated area away from moisture, sources of				
	heat, open flames, food and drink. Keep adequate clearance between walls and batteries.				
	Temperature above 90°C may result in battery leakage and rupture. Since short circuit can				
	cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do				
	not jumble them.				
Other	Manufacturer recommendations regarding maximum recommended currents and operating				
	temperature range.				
	Applying pressure on deforming the battery may lead to disassembly followed by eye, skin				
	and throat irritation.				

## **Section 8: Exposure Controls/Personal Protection**

Respiratory protection:	Not necessary under normal use.		
	In case of battery rupture, use self-contained full-face respiratory equipment with		
	type ABEK filter.		
Hand protection:	Not necessary under normal use.		
	Use rubber gloves if handling a leaking or ruptured battery.		
Eye protection:	Not necessary under normal use. Wear safety goggles or glasses with side shields if handling a leaking or ruptured battery.		
Skin protection:	Not necessary under normal use. Use rubber apron and protective working in case of handling of a ruptured battery.		

## **Section 9: Physical and Chemical Properties**

# 9.1 Information on basic physical and chemical properties Appearance

**Description**: Solid **Color**: Not available

Product Name: Lithium-Ion Battery

MSDS Page 5 of 9



Odor: Odorless

Odor threshold: Not available

pH: Not available

Melting point/freezing point: Not available

Initial boiling point and boiling range: Not available

Flash point: Not available

Evaporation rate: Not available

Flammability (solid, gas): Not available

Upper/lower flammability or explosive limits: Not available

Vapor pressure: Not available

Solubility (ies): insoluble.

Vapor density: Not available

Relative density: Not available

Partition coefficient: n-octanol/water: Not available

Auto ignition temperature: Not available

**Decomposition temperature:** Not available

Viscosity: Not available

**Explosive properties :** Not available **Oxidizing properties :** Not available

Molecular weight: Not available

## 9.2 Other information

Not available

## Section 10: Stability and Reactivity

#### 10.1 Reactivity

- Stable at ambient temperature.

## 10.2 Chemical stability

- There is no hazard when the measures for handling and storage are followed.
- Stable under normal temperatures and pressures.

#### 10.3 Possibility of hazardous reactions

- Will not occur under normal conditions.
- In case of cell damage, possible release of dangerous substances and a flammable gas mixture.
- Containers may explode when heated.
- Fire may produce irritating and/or toxic gases.
- Some liquids produce vapors that may cause dizziness or suffocation.
- Inhalation of material may be harmful.

Product Name: Lithium-Ion Battery

MSDS Page 6 of 9



## 10.4 Conditions to avoid

- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Friction, heat, sparks or flames
- Dusts or shavings from borings, turnings, cuttings, etc.
- Do not exceed manufacturer's recommendation for charging or use battery for an application for which it was not specifically designed.
- Do not electrically short.

## 10.5 Incompatible materials

- Avoid contact with acids and oxidizers.
- Keep away from any possible contact with water, because of violent reaction and possible flash fire.
- Handle under inert gas. Protect from moisture.
- Combustibles, reducing agents

## 10.6 Hazardous decomposition products

- None under normal conditions.
- Corrosive and/or toxic fume
- Material may produce irritating and highly toxic gases from decomposition by heat and combustion during burning.
- Irritating and/or toxic gases

## **Section 11: Toxicological Information**

When properly used or disposed, the LITHIUM-ION batteries do not resent environmental hazard.

If the cells are opened through misuse or damage, discard immediately. Internal components of cells are irritants and sensitizers.

## **Section 12: Ecological Information**

When properly used or disposed, the LITHIUM-ION batteries do not resent environmental hazard.

Persistence/degradability: do not bury or throw out into the environment.

## **Section 13: Disposal Considerations**

Dispose in accordance with applicable regulations which vary from country to country. (In more countries, the thrashing of used batteries is forbidden, and the end-users are invited to dispose them properly, eventually through not-for-profit organizations, mandated by local governments or organized on a voluntary basis by professionals).

Lithium-Ion batteries should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal.

**13.1 Incineration:** Incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.

Product Name: Lithium-Ion Battery

MSDS Page 7 of 9

Issue date: 02/12/2019

Version #: 1.0



## 13.2 Land filling: Leach ability regulations (mg/l)

Component	Leach ability EC limit	EPA	Other*
Iron	100		5
Nickel	500	2	0.5

13.3 Recycling: Send to authorized recycling facilities, eventually through licensed waste carrier.

## **Section 14: Transport Information**

## **SHIPPING BY AIR**

14.1UN Number: 3480

14.2UN Proper shipping name: LITHIUM ION BATTERIES

14.3 Transport Hazard class: 9

14.4 Packing group : II

14.5 Environmental hazards: No

14.6IATA Transport: PI 965-Section IB (≤100Wh) or PI 965-Section IA (>100Wh)

## **SHIPPING BY SEA**

14.1UN Number: 3480

14.2UN Proper shipping name: LITHIUM ION BATTERIES

14.3 Transport Hazard class: 9

14.4 Packing group: II

14.5 Environmental hazards: No

**14.6IMDG Transport** : SP188 (≤100Wh) or P903 (>100Wh)

## **Section 15: Regulatory Information**

《Classification, Labeling and Packaging Regulation》

《REACH (EC)1907/2006》

《Dangerous Goods Regulation》

《Recommendations on Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substances Control Act》 (TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》(CWA)

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws

Product Name: Lithium-Ion Battery

MSDS Page 8 of 9



## **Section 16: Other Information**

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

FULBAT does not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. FULBAT does not offer warranty against patent infringement. Additional information is available by calling the telephone number above designated purpose.

Prepared and approved by FULBAT S.a.s

Product Name: Lithium-Ion Battery

MSDS Page 9 of 9